50X1	CONFIDENTIAL		
,,,,,		50X1	
	COUNTRY Czechoslovakia/Austria	DATE DISTR. 25 Nev	. 1953
	SUBJECT Proposed Oil Drilling Sites	NO. OF PAGES 5	
50X1	ploneida	NO. OF ENCLS. 2 (LISTED BELOW)	
50X1		SUPPLEMENT TO REPORT NO.	
			(
	THIS IS UNEVALUATED INFORMATION		50X1

1. Identification Data:

50X1

Reference Encl. 1, Overlay Sheet W-ll Pinpoint Location of Proposed Drilling Sites and nearby Villages from Malacky, Czechoslovakia to Vienna, Austria.

- Pt. # 1. Malacky /N 48-26, E 17-017: approximately 10,000 population, northeast of Hostetno /Pt. 57. The line of possible drilling sites and oil fields started here.
 - # 2. Plavecky Styrtok \sqrt{N} 48-22, E 17-007: approximately 1,000 to 2,000 population. Proposed site for future drilling.
 - # 3. Lab \sqrt{N} 48-22, E 16-597: approximately 2,000 population. Oil field located here was in production in July 1953. There were three oil well derricks located in Lab vicinity. One of the three derricks was located in the center of village.
 - # 4. Line of Possible Future Development: approximate location of drilling sites and oil fields extending from Malacky, Czechoslovakia to Vienna, Austria.

CONFIDENTIAL



CONFIDENTIAL

50X1

Hostetno /N 48-20, E 16-557: approximately 3,000 popula-Pt. # 5. 60 border guards in this tion. village. 50X1 the line of drilling sites /Pt. 4/, extending 50X1 from Malacky to Vienna

- River Morava: approximately 20 to 30 m. wide, three to # 6. 50X1 four meters deep, fairly strong current. water looked clear, except for oil slick. In rainy sesson February, March and April river would overflow and In rainy seaflood. In winter months the river would freeze over but the ice was not thick enough for a person to walk on.
- approximately 4,000 popula-Marchegg \sqrt{N} 48-17, E 16-557: # 7. tion.
- Road: concrete, three to four meters wide, good condi-#8. tion, led from Marchegg to Vienna, medium traffic.
- Four Oil Field Derricks: steel construction, approximately 30 to 40 m. high. The power source consisted of two # 9. diesel motors. Two motors for pumping mud were approximately eight meters away from rig (Soviet type). well A was in production as of July 26, but well B was still in the drilling stage. The drilling crew consisted of four men per shift, supported by 10-15 crew men. No information as to depth or stage of drilling development, due to complete security measures. Guarded by civilian police and dogs.
- Zwerndorf \sqrt{N} 48-21, E 16-507: small farming village, possible future drilling site.
- Stripfing \sqrt{N} 48-21, E 16-487: possible future drilling site. small farming village, # 11.
- Weikendorf \sqrt{N} 48-21, E 16-467: small farming village, possible future drilling site. # 12.
- Gaenserndorf \sqrt{N} 48-20, E 16-437: small farming village, possible future drilling site. # 13.
- Strasshof /N 48-19, E 16-387: small farming village, # 14. possible future drilling site.
- Railroad: double track, normal European gauge, telephone # 15. wires along tracks.
- # 16. Four Oil Well Derricks: located near Vienna.
- Vienna, Austria \sqrt{N} 48-16, E 16-347: oil field located near this city. End of line of oil sites. # 17.
- In the first stage, six or seven men operated a portable mobile rig for drilling test holes. Core samples were taken frequently for a microscopic examination by a geologist. a Soviet geologist at the drilling site talking to the driller. samples showed possibilities of future production a large rig was brought in to drill the well. The rigs were about 30 to 50 m. high, steel, Soviet rotary type drills. The drill stem pipe was 10 to 20 cm. in diameter, rig was powered by two large diesel units of Soviet origin, about two meters away from rig. About eight meters away from rig were two more diesel units used to pump drilling mud from

CONFIDENTIAL

50X1

50X1

50X1

50X1



Declassified in Part - Sanitized Copy Approved for Release @ 50-Yr 2013/07/12 : CIA-RDP82-00046R000200340012-9

CONFIDENTIAL

50X1

the slush pit into the drill stem. Total depth of hole was usually from 1,000 to 2,000 m. Drilling crew consisted of a driller, two roughnecks and a towerman.

if the bedrock was soft the gas would escape in the surrounding area and could not be utilized. In such instances the wells had to be cemented before being put into production.

Enclosures:

- 1. Pinpoint Location of Proposed Drilling Sites
- 2. Construction of Derrick for Drilling of Nafty

CONFIDENTIAL




CONFIDENTIAL

50X1

ENCLOSURE 2:

Construction of Derrick for Drilling of Nafty






CONFIDENTIAL
SECURITY INFORMATION

-4-

ENCI. 1



CONFIDENTIAL SECURITY INFORMA

PLANECKY STURTOK

Hochstetno

Marchegg

GANGERNUF

Welkende Stripfing